



KTECH

K TECH GROUP PTE. LTD.

407 Ang Mo Kio Ave 10 #01-759 Singapore 560407

Tel no : (+65) 6570 0887

Website : www.ktech.asia

Email : Sales@ktech.asia

NX44DLHF

1.3Megapixel HD Network Dome Camera



Features

- H.264 IP CAMERA 1.3MP
- IR LED: 24PCS LED lights
- IR range: up to 60M
- varifocal Lens 2.8-12mm lens, with internal POE,aslo need DC port
- Housing with plastic , IP66

**KTECH****K TECH GROUP PTE. LTD.**

407 Ang Mo Kio Ave 10 #01-759 Singapore 560407

Tel no : (+65) 6570 0887

Website : www.ktech.asia

Email : Sales@ktech.asia

NX44DLHF**Technical Specifications**

Model/Specification		NX44DLHF
Camera	Image Sensor	1/3"CMOS
	Resolution	1280×960
	Pixels	1.3MP
	Compression	H.264/JPEG
	Frame Rate	25fps~30fps
	Bitrate	204Kbps~6Mbps
	Synchronization	Internal
	SNR	55.7dB
	Min Illumination	0Lux(IR ON)
Lens	Lens Mount	M12
	Lens	varifocal 2.8-12mm
	Focus Control	Manual
Function	Exposure Mode	Auto
	Gain Control	Auto
	White Balance	Auto
	Digital noise reduction	3D DNR
	OSD	Support
	Network TimeSyn	Support
	QR Code	Support generate device qr code for scanning to add
	Scheduled Restart	Support
	ROI	Support
	IR Sensitivity	Adjustable
	Defog	Support
	Privacy Mask	Support 4 rectangle areas
	Motion Detection	Support
	Video Adjust	Supports contrast, brightness,saturation, sharpness adjustment
Scene	Support Indoor、Outdoor、Default、 Soft scenes	
Day & Night	IR cut filter with auto switch, Support Color to Black	

*Design and Specifications are subject to change without notice. ©2015 K TECH GROUP PTE.LTD.



K TECH

K TECH GROUP PTE. LTD.

407 Ang Mo Kio Ave 10 #01-759 Singapore 560407

Tel no : (+65) 6570 0887

Website : www.ktech.asia

Email : Sales@ktech.asia

NX44DLHF

	Electronic screen	Support Exposure time setting, solve view electronic screen problem
	Night Self-Adaption	Support
	Wide Dynamic Range	Digital WDR
	Image setting	Mirror、Rotate
	IP Self-Adaption	Support
	Alarm	E-mail、Client
	Remote Operation	System、Stream、User、Network Management
	External Interface	Support Audio Input
Network	Ethernet	1 RJ45 10M/100M Adaptive Ethernet Interface
	Tri-Stream	Support
	Protocol	Support HTTP,TCP/IP,ICMP,RTSP,RTP,UDP,RTCP, SMT P,FTP,DHCP,DNS,PPPOE
	System Compatibility	ONVIF 2.4
	Transmission	Internal Cloudsee Protocol
	Browser	IE8+,Chrome18+,Firefox5.0+,Safari5.02+ browsers
	Connection	32CH
	User Permission	Up to 13 users, Three level authority: Administrator、User、Visitor
General	Infrared Lamp	24pcs LED Lamps
	IR Distance	20m
	Waterproof	IP66
	Power Supply	DC 12V
	PoE Power	Optional
	Working Temperature	-20°C~+55°C
	Working Humidity	10%~90%
	Power	Day: <3W Night: <6W
	Material	Aluminum
	Weight (g)	600g
	Installation	Ceil Mounting